

TECHNICAL DATA SHEET

COLD-BOX PROCESS



Member of 汉高 Group

1 / 2

Sigmacure 120 UCB Pt 1

Sigmacure 120 (SC 120) Phenolic Urethane Part 1 Resin has been designed to offer high tensile strength development and good bench life performance, particularly at elevated sand temperatures. SC 120 can be used with several different Part 2 Isocyanate components, chosen depending upon the desired performance features. When used with Sigmacure 210 Part 2 Resin, a system with particularly good performance at high ambient and sand temperatures is obtained.

FIELD OF APPLICATION

SC 120 is suitable for all metal casting applications. Features available when using SC 120 with the appropriate Part 2 component include the following:

- Superior performance on hot sand
- High tensile strength development
- Extended bench life of mixed sand (minimal down time)
- Good hot strength and humidity resistance
- Fast cure speeds (high productivity)

PRODUCT CHARACTERISTICS

Relative Density	9.09	Flash Point, F ^o , TCC	>156
Viscosity, cps	110	Refractive Index	1.5640

PROCESSING / NOTES ON USE

Sigma Cure 120 is a phenolic resin used in conjunction with an MDI-type isocyanate resin, such as Sigma Cure 210. Both the Part 1 and Part 2 resin components are mixed with a new silica or lake sand, or a reclaimed sand, in ratios ranging from 50/50 to 60/40, and at a total resin content in the range of 0.8 % to 2.0 % based on the weight of the sand. The resulting sand mix is then blown into a core box and subsequently cross linked by passage of a vaporized tertiary amine catalyst such as, dimethylisopropylamine (DMIPA) or dimethylpropylamine (DMPA), to produce a urethane bond.

TRANSPORT AND STORAGE

Recommended storage temperature is between 60 - 90°F. At lower temperatures, viscosity will increase, making pumping and mixing more difficult. Freezing temperatures should be avoided. At high temperatures solvent loss can occur. Drum storage should be in a dry area, out of direct sunlight. Partially used drums should be tightly closed to prevent contamination, primarily from water, which can adversely affect performance. The recommended stock rotation is six months when properly stored.

PACKAGING

Pail	Drum	IBC (Tote)	Bulk Tank
------	------	------------	-----------

CORRESPONDING PRODUCTS

Sigmacure 210 UCB Pt2

Sigmacure 120 P1

TECHNICAL DATA SHEET

COLD-BOX PROCESS



Member of 汉高 Group

2 / 2

SAFE HANDLING

Chemically resistant gloves and eye protection should be used when handling or using chemical binders. Material Safety Data Sheets are available for all products. Drum labels also contain handling information. Part 1 will react with the Part 2 component, without catalyst, in an exothermic reaction, to give a solid polymer. Do not mix Part 1 and Part 2 except on sand during use. Please refer to the Material Safety Data Sheet for additional information.

**FOR EMERGENCY MEDICAL ASSISTANCE PLEASE CALL: Health and Safety Information Services
1-866-595-5738**

TECHNICAL SERVICE

Let HA International be “The Best Total Solution” for your foundry by providing innovative products, in-depth technical assistance, and a diverse product line specially formulated for any foundry application. Both our in-house and field experts are available to assist you with your most challenging foundry applications. Please contact your sales representative for additional technical information.

The above data are for description purposes only. They are not intended and may not be construed to represent a warranty of specific product or application properties or a warranty of usability for a specific purpose. Any statements about our products reflect our current state of knowledge and do not create any legally binding obligations. They do not limit any of the buyer's obligation under law or contract to test the delivered products for usability for the intended purpose. The safety data sheet must be observed. All product liability or warranty claims are explicitly excluded if the specific application of our product has not been approved by us. In addition our general terms and conditions for sales and delivery apply.

Sigmacure 120 P1

HA International
630 Oakmont Lane – Westmont, IL
Tel. +800-323-6863 |

Sales@ha-international.com
www.ha-international.com